STAHLWILLE()®



Motorised calibrating and adjusting tool from 1 to 400 N·m

7794-2

Art.No. 96521093

GTIN **4018754214891**

Model 7794 - 2

perfect (Introl

Label.

Features.

Motor-driven calibration and adjustment device Measuring r.1-400N·m for transducers 7728 (sizes 1-100)

The electronic perfectControl® calibrating unit with its electric drive considerably reduces the amount of effort and time required for calibration and adjustment tasks on torque wrenches

- · measurement possible without moving the point of application of force
- prevents faulty readings thanks to precision-mounted spindle and finely regulated motor
- extremely accurate calibration thanks to optimised bearings and square drives for the transducers
- rapid, easy change of transducers thanks to quick-release latching system
- convenient pushbutton controls for clockwise and anticlockwise measurements with automatic speed compensation
- saves time because the bridge support is locked in place using a single-handed eccentric lever
- transmission of readings to a PC via USB interface for further processing, analysis and archiving
- a Declaration of Conformance or a calibration certificate can be printed or saved as a PDF file after calibration
- · as found / as left calibrations can be documented
- during calibration, DIN EN ISO 6789:2003 in numerous languages is supported. Additional standards and works standards are available on request
- can be upgraded to perfectControl calibrating unit No 7794-3 for angle-controlled wrenches
- calibration up to 1000 N·m is possible using the easily attached extension unit No 7791-1
- · design patent
- protected by national and international patents
- · both clicking and indicating torque wrenches can be calibrated
- calibration of transducers is possible using reference torque wrenches No 7770-10, 7770-100 and 7770-1000, available on request.
- the unit is supplied without the torque wrench, transducers or notebook
- transducers laboratory No 7728

Content:

6 calibrating square drive insert tools No 734K (sizes 4, 5, 12, 20, 40, 100) 6 square drive adaptors (No 409M, No 7787, No 7788, No 7789, No 7789-4, No 7789-5)

- 1 USB adaptor No 7757-1
- 1 software Torkmaster 7731-1
- 1 jack cable No 7751
- 1 spiral cable No 7752
- 1 spiral cable No 7751-2 with jack plug and self-locking precision plug
- 1 low-temperature cable connector
- 1 hexagon key wrench No 10760CV 2 mm are included

Advantages.

The electronic perfectControl® calibration device with electric drive significantly reduces the effort and time required for calibrations and adjustments of torque wrenches

Intelligent and low maintenance design, which means measurement errors caused by incorrect operation are almost impossible.

In conjunction with the TorkMaster software, calibration certificates are issued in no time at all.

Calibrations up to 1000 N·m using easy-to-install extension No. 7791-1.

USB interface for data exchange with the PC.









Product highlights.



Precision measurements.

perfectControl calibration devices guarantee controlled, reproducible force application and provide accurate measurement results in conjunction with STAHLWILLE measurement devices and safe handling of the tool. All measurements are made without shifting the force application point. PerfectControl calibration devices guarantee controlled, reproducible force application and provide accurate measurement results in conjunction with STAHLWILLE measurement devices and safe handling of the tool. All measurements take place without shifting the force application point.



Extremely efficient thanks to motorised operation.

The electrically powered perfectControl 7794-2 reduces the amount of effort and time required to produce reproducible results.



Comfortable and intuitive handling.

The QuickRelease technology allows the measurement devices to be exchanged quickly. The bridge attachment for torque wrenches can be adjusted with one hand using an eccentric tensioner. Actions and directions are easy to set using buttons.



Modular and versatile.

The perfectControl basic versions calibrate torque wrenches up to 400 N·m. Extending with module 7791-1 makes calibrations up to 1,000 N·m possible. The perfectControl basic versions calibrate torque wrenches up to 400 N·m. Extending with module 7791-1 makes calibrations up to 1,000 N·m possible



Calibration certificates in an instant.

The USB interface makes exchanging data with the PC seamless. In conjunction with the TorkMaster software, calibration certificates are issued in no time at all. The USB interface makes exchanging data with the PC seamless. In conjunction with the TorkMaster software, calibration certificates are issued in no time at all.



Even more possibilities.

Additional modules such as connecting to CAQ systems with an automated interface or advanced methods such as machine capability testing (MFU) are available by request.

Technologies and features.



QuickRelease

The QuickRelease technology ensures tools cannot be inadvertently lost – while enabling rapid, safe tool changes.

Technical Attributes.

Logistics data.

Range N·m	1-400 N·m	Depth mm (IFS)	1200
Width mm (b)	640 mm	Width mm (IFS)	800
Functional length (LF) max.	815 mm	Height mm (IFS)	820
mm		Length (packed, mm)	1200
for transducers	7728 (sizes 1-100)	Width (packed, mm)	800
Height mm (h)	328 mm	•	

Profile width 180 mm Volume (packed, dm3) 787.2 dm3 Art. no. 96521093 Weight (gross, kg) 62,200 Weight PAP (kg) 0,000 Weight PVC (kg) 0,000 GTIN 4018754214891 Country of origin GERMANY Region of origin Nordrhein-Westfalen WEEE/ElektroG Großgeräte B2B Customs tariff no. 90319000 Packing standard 1 Weight 51500 g	Length mm (L)	1060 mm	Height (packed, mm)	820
Weight (gross, kg) 62,200 Weight PAP (kg) 0,000 Weight PVC (kg) 0,000 GTIN 4018754214891 Country of origin GERMANY Region of origin Nordrhein-Westfalen WEEE/ElektroG Großgeräte B2B Customs tariff no. 90319000 Packing standard 1	Profile width	180 mm	Volume (packed, dm3)	787.2 dm3
Weight PAP (kg) 0,000 Weight PVC (kg) 0,000 GTIN 4018754214891 Country of origin GERMANY Region of origin Nordrhein-Westfalen WEEE/ElektroG Großgeräte B2B Customs tariff no. 90319000 Packing standard 1			Art. no.	96521093
Weight PVC (kg) 0,000 GTIN 4018754214891 Country of origin GERMANY Region of origin Nordrhein-Westfalen WEEE/ElektroG Großgeräte B2B Customs tariff no. 90319000 Packing standard 1			Weight (gross, kg)	62,200
GTIN 4018754214891 Country of origin GERMANY Region of origin Nordrhein-Westfalen WEEE/ElektroG Großgeräte B2B Customs tariff no. 90319000 Packing standard 1			Weight PAP (kg)	0,000
Country of origin Region of origin WEEE/ElektroG Customs tariff no. Packing standard GERMANY Nordrhein-Westfalen Großgeräte B2B 90319000 1			Weight PVC (kg)	0,000
Region of origin WEEE/ElektroG Customs tariff no. Packing standard Nordrhein-Westfalen Großgeräte B2B 1			GTIN	4018754214891
WEEE/ElektroG Großgeräte B2B Customs tariff no. 90319000 Packing standard 1			Country of origin	GERMANY
Customs tariff no. 90319000 Packing standard 1			Region of origin	Nordrhein-Westfalen
Packing standard 1			WEEE/ElektroG	Großgeräte B2B
. Some state of the state of th			Customs tariff no.	90319000
Weight 51500 g			Packing standard	1
			Weight	51500 g

Variants.

Art. no.	Art. no. (ERP)	Description	GTIN
96521093	7794 - 2	Motor-driven calibration and adjustment device Measuring r.1-400N·m for transducers 7728 (sizes 1-100)	4018754214891

GTIN-Code.



Accessories.



