



### Torque wrench

#### 730a/2 Quick

Art.No. 50584002

GTIN **4018754292684**Model **730A/2 QUICK** 

Label.

click-type

Features.

• the measuring element is only under load while force is being applied, no need for manual reset to zero

Torque wrench service MANOSKOP® (in·lb) No. 730a/2 Quick Measuring r. 30-175in

- mount for interchangeable insert/shell tools
- QuickRelease safety lock (sizes 5-65)

lb Tool holders 9 x 12 mm L. 179mm

- rapid setting thanks to easy-action locking lever in the handle (sizes 5-65)
- · ergonomically designed, non-slip adjuster with a thumb recess
- · magnifying glass integrated in the display window
- · optimised convex handle for strain-free working
- · dual stop signal
- twin scales N·m/ft·lb and N·m/in·lb (sizes 5–80)
- on request also available as an N·m-only version without twin scale (sizes 5-65)
- can be applied for either clockwise or anticlockwise tightening by turning the inserts over
- any force applied to the tool after the 'click' or applied in the opposite direction to the current function – e.g. forcible loosening of a jammed screw - does not act on the trigger mechanism and cannot cause damage to it
- calibration using perfectControl® calibrating unit No 7794 or calibration system No 7706. Readjustment does not require disassembly.
- certificate in accordance with DIN EN ISO 6789-2:2017
- display deviation value ± 4%

## Advantages.

Releasing.

## Product highlights.



#### Fast.

Rapid setting thanks to the easy-action locking lever in the handle. Ergonomically designed, non-slip adjuster with a thumb recess for fast, safe setting of the slider.



#### Simple.

Quick adjustment from outside, no disassembly of the torque wrench required, with two adjustment points for the maximum & minimum values.



### Flexible rod principle.

Mechanical torque wrenches from STAHLWILLE have a wear-resistant trigger system with a ¢exible rod. In contrast to conventional torque wrenches with spiral springs, the STAHLWILLE system eliminates one key work step: once the fastener has been tightened, it is not necessary to reset the wrench to »0«.

## Technologies and features.



#### QuickRelease


The QuickRelease technology ensures tools cannot be inadvertently lost – while enabling rapid, safe tool changes.




### **Tool Control System**

Safety-conscious inlays - designed to fit our Tool Trolleys and Tool Boxes. With yellow signal cut-outs to show whether all the tools are in their places.

# Technical Drawing.





# **Technical Attributes.**

30-175 in∙lb
27,5 mm
a/2
9 x 12 mm
23,6 mm
179 mm
157,2 mm
17,5 mm
5 in·lb

# Logistics data.

Depth mm (IFS)	180
Width mm (IFS)	40
Height mm (IFS)	30
Length (packed, mm)	220
Width (packed, mm)	60
Height (packed, mm)	60
Volume (packed, dm3)	0.792 dm3
Art. no.	50584002
Weight (gross, kg)	0,396
Weight PAP (kg)	0,000
Weight PVC (kg)	0,006
GTIN	4018754292684
Country of origin	GERMANY
Region of origin	Nordrhein-Westfalen
WEEE/ElektroG	nicht ear-pflichtig
Customs tariff no.	82041100
Packing standard	1
Weight	315 g

## Variants.

Art. no.	Art. no. (ERP)	Description	GTIN
50584004	730A/4 QUICK	Torque wrench service MANOSKOP® (in·lb) No. 730A/4 Quick Measuring r. 70-350in lb Tool holders 9 x 12 mm L. 223mm	4018754292691

	50584002	730A/2 QUICK	Torque wrench service MANOSKOP® (in·lb) No. 730a/2 Quick Measuring r. 30-175in lb Tool holders 9 x 12 mm L. 179mm	4018754292684
-	50584001	730A/2-1 QUICK	Torque wrench No. 730 Quick Measuring r. 17,5-87,5in lb Tool holders 9 x 12 mm L. 179mm	4018754292677

### GTIN-Code.

