

Angle torque wrench MANOSKOP®

714R



Art.No. **96501010**
GTIN **4018754212750**
Model **714R/10**

Label. Angle torque wrench MANOSKOP® No. 714R Measuring r. 10-100N·m Drive 1/2 L. 500mm

Product highlights.



PRODUCT IMAGE
IN PROGRESS

Audited.

All our angle-controlled torque wrenches have a logging function. Using the corresponding software (this is an optional extra), it is possible to read out programmed, stored readings and archive them on the PC – for example by the serial number of the tool, date and timestamp of the tightening operation, target torque and angle and the torques and angles actually recorded.



PRODUCT IMAGE
IN PROGRESS

Electromechanical triggering.

The best of both worlds: electromechanical torque wrenches from STAHLWILLE combine the uncompromising accuracy of an electronic torque tool with the comforting tactile feedback of a mechanical trigger mechanism.



PRODUCT IMAGE
IN PROGRESS

Logging function.

Comprehensive documentation options. As many as 2000 tightening actions can be stored with timestamps.



PRODUCT IMAGE
IN PROGRESS

Versatile.

Three function modes: first peak, peak (indicating mode) and track (indicating mode).

PRODUCT IMAGE
IN PROGRESS**Even more possibilities.**

Additional modules such as connecting to CAQ systems with an automated interface or advanced methods such as machine capability testing (MFU) are available by request.

PRODUCT IMAGE
IN PROGRESS**Even more possibilities.**

Additional modules such as connecting to CAQ systems with an automated interface or advanced methods such as machine capability testing (MFU) are available by request.

Technologies and features.

**QuickRelease**

The QuickRelease technology ensures tools cannot be inadvertently lost – while enabling rapid, safe tool changes.



Technical Attributes.

Measuring range N·m	10-100 N·m
Measuring range ft·lb	7,4-75 ft·lb
Measuring range in·lb	90-900 in·lb
External square drive (inch)	1/2
Battery type	Micro-NiMH AAA, 1.2V
Width mm (b)	80 mm
Weight with box	1657 g
Size	10
Size square socket [inside square drive]	9 x 12 mm
Height mm (h)	70 mm
Length mm (L)	500 mm

Logistics data.

Depth mm (IFS)	680
Width mm (IFS)	80
Height mm (IFS)	70
Length (packed, mm)	680
Width (packed, mm)	80
Height (packed, mm)	70
Volume (packed, dm ³)	3.808 dm ³
Art. no.	96501010
Weight (gross, kg)	1,955
Weight PAP (kg)	0,130
Weight PVC (kg)	0,000
GTIN	4018754212750
Country of origin	GERMANY
Region of origin	Nordrhein-Westfalen
WEEE/ElektroG	Großgeräte B2C

Customs tariff no.	82041100
Packing standard	1
Weight	1232 g

Variants.

Art. no.	Art. no. (ERP)	Description	GTIN
96501001	714R/ 1	Angle torque wrench MANOSKOP® No. 714R Measuring r. 1-10N·m Drive 1/4 L. 269mm	4018754212712
96501002	714R/ 2	Angle torque wrench MANOSKOP® No. 714R Measuring r. 2-20N·m Drive 1/4 L. 269mm	4018754212729
96501004	714R/ 4	Angle torque wrench MANOSKOP® No. 714R Measuring r. 4-40N·m Drive 1/4 L. 295mm	4018754212736
96501006	714R/ 6	Angle torque wrench MANOSKOP® No. 714R Measuring r. 6-60N·m Drive 3/8 L. 427mm	4018754212743
96501010	714R/10	Angle torque wrench MANOSKOP® No. 714R Measuring r. 10-100N·m Drive 1/2 L. 500mm	4018754212750
96501020	714R/20	Angle torque wrench MANOSKOP® No. 714R Measuring r. 20-200N·m Drive 1/2 L. 594mm	4018754212767
96501040	714R/40	Angle torque wrench MANOSKOP® No. 714R Measuring r. 40-400N·m Drive 3/4 L. 737mm	4018754212774
96501065	714R/65	Angle torque wrench MANOSKOP® No. 714R Measuring r. 65-650N·m Drive 3/4 L. 980mm	4018754212781
96501080	714R/80	Angle torque wrench MANOSKOP® No. 714R Measuring r. 80-800N·m Drive 3/4 L. 1253mm	4018754212798
96501100	714R/100	Angle torque wrench MANOSKOP® No. 714R Measuring r. 100-1000N·m Drive 3/4 L. 1438mm	4018754212804

GTIN-Code.



Accessories.



96521161
Interface adaptor set



52110061
Interface adaptor



52110220
Bluetooth module für
torque wrenches

Images.

