

## Angle torque wrench MANOSKOP®

714R



Art.No. 96501006  
GTIN 4018754212743  
Model 714R/ 6

**Label.** Angle torque wrench MANOSKOP® No. 714R Measuring r. 6-60N·m Drive 3/8 L. 427mm

## Product highlights.



PRODUCT IMAGE  
IN PROGRESS

### **Audited.**

All our angle-controlled torque wrenches have a logging function. Using the corresponding software (this is an optional extra), it is possible to read out programmed, stored readings and archive them on the PC – for example by the serial number of the tool, date and timestamp of the tightening operation, target torque and angle and the torques and angles actually recorded.



PRODUCT IMAGE  
IN PROGRESS

### **Electromechanical triggering.**

The best of both worlds: electromechanical torque wrenches from STAHLWILLE combine the uncompromising accuracy of an electronic torque tool with the comforting tactile feedback of a mechanical trigger mechanism.



PRODUCT IMAGE  
IN PROGRESS

### **Logging function.**

Comprehensive documentation options. As many as 2000 tightening actions can be stored with timestamps.



PRODUCT IMAGE  
IN PROGRESS

### **Versatile.**

Three function modes: first peak, peak (indicating mode) and track (indicating mode).



**Even more possibilities.**

Additional modules such as connecting to CAQ systems with an automated interface or advanced methods such as machine capability testing (MFU) are available by request.



**Even more possibilities.**

Additional modules such as connecting to CAQ systems with an automated interface or advanced methods such as machine capability testing (MFU) are available by request.

## Technologies and features.



**QuickRelease**

The QuickRelease technology ensures tools cannot be inadvertently lost – while enabling rapid, safe tool changes.



## Technical Attributes.

Measuring range N·m	6-60 N·m
Measuring range ft·lb	4,5-45 ft·lb
Measuring range in·lb	54-540 in·lb
External square drive (inch)	3/8
Battery type	Micro-NiMH AAA, 1.2V
Width mm (b)	80 mm
Weight with box	1390 g
Size	6
Size square socket [inside square drive]	9 x 12 mm
Height mm (h)	70 mm
Length mm (L)	427 mm

## Logistics data.

Depth mm (IFS)	560
Width mm (IFS)	80
Height mm (IFS)	70
Length (packed, mm)	560
Width (packed, mm)	80
Height (packed, mm)	70
Volume (packed, dm3)	3.136 dm3
Art. no.	96501006
Weight (gross, kg)	1,675
Weight PAP (kg)	0,095
Weight PVC (kg)	0,000
GTIN	4018754212743
Country of origin	GERMANY
Region of origin	Nordrhein-Westfalen
WEEE/ElektroG	Kleingeräte B2C

<b>Customs tariff no.</b>	82041100
<b>Packing standard</b>	1
<b>Weight</b>	965 g

## Variants.

Art. no.	Art. no. (ERP)	Description	GTIN
96501001	714R/ 1	Angle torque wrench MANOSKOP® No. 714R Measuring r. 1-10N·m Drive 1/4 L. 269mm	4018754212712
96501002	714R/ 2	Angle torque wrench MANOSKOP® No. 714R Measuring r. 2-20N·m Drive 1/4 L. 269mm	4018754212729
96501004	714R/ 4	Angle torque wrench MANOSKOP® No. 714R Measuring r. 4-40N·m Drive 1/4 L. 295mm	4018754212736
96501006	714R/ 6	Angle torque wrench MANOSKOP® No. 714R Measuring r. 6-60N·m Drive 3/8 L. 427mm	4018754212743
96501010	714R/10	Angle torque wrench MANOSKOP® No. 714R Measuring r. 10-100N·m Drive 1/2 L. 500mm	4018754212750
96501020	714R/20	Angle torque wrench MANOSKOP® No. 714R Measuring r. 20-200N·m Drive 1/2 L. 594mm	4018754212767
96501040	714R/40	Angle torque wrench MANOSKOP® No. 714R Measuring r. 40-400N·m Drive 3/4 L. 737mm	4018754212774
96501065	714R/65	Angle torque wrench MANOSKOP® No. 714R Measuring r. 65-650N·m Drive 3/4 L. 980mm	4018754212781
96501080	714R/80	Angle torque wrench MANOSKOP® No. 714R Measuring r. 80-800N·m Drive 3/4 L. 1253mm	4018754212798
96501100	714R/100	Angle torque wrench MANOSKOP® No. 714R Measuring r. 100-1000N·m Drive 3/4 L. 1438mm	4018754212804

## GTIN-Code.



## Accessories.



96521161  
Interface adaptor set



52110061  
Interface adaptor



52110220  
Bluetooth module für  
torque wrenches

## Images.

