

Standard MANOSKOP® torque wrench w.permanently installed QuickRelease ratchet



721QR/15 Quick

 Art.No.
 50204115

 GTIN
 4018754268955

 Model
 721QR/15 QUICK



Label.

Features.

MANOSKOP® torque wrench No. 721QR/15 Quick Measuring r. 30-150N·m Drive 1/2 L. 452,5mm

- Triggering
- Flash adjustment by easy-to-operate clamping lever in the handle
- ergonomically shaped, non-slip adjustment element with thumb recess
- integrated magnifying glass in the reading window
- optimised ball handle for fatigue-free working
- double stop signal
- double scale N·m/ft·lb
- no resetting to "0" required, since the measuring element is only loaded during the tightening process
- Continued loading after release or loads in the opposite direction to the functional direction, e.g. in the case of stuck bolts.
- Continued load after triggering or loads against the functional direction, e.g. with stuck screws, do not act on the trigger mechanism, which is thus protected against damage.
- Protection of all sensitive parts by the robust steel tube housing
- Calibration with the perfectControl calibration device no. 7794 or the calibration system no. 7706. If necessary, readjustment without disassembly.
- Display deviation ± 4 %
- With certificate

Advantages.

Fast setting with easy-to-operate clamping lever in the handle, integrated lens for better readability of the set value

Ergonomically shaped, non-slip adjustment element with thumb recess and optimised ball handle for fatigue-free work Efficient. No reset to "0" necessary, as measuring element is only strained during the tightening process

Releasing torque wrench with permanently installed 1/2" QuickRelease ratchet, double stop signal (tactile and audible), left-hand tightening by turning over the plug-in tools

Product highlights.



Flexible rod principle.

Mechanical torque wrenches from STAHLWILLE have a wear-resistant trigger system with a ¢exible rod. In contrast to conventional torque wrenches with spiral springs, the STAHLWILLE system eliminates one key work step: once the fastener has been tightened, it is not necessary to reset the wrench to »0«.

Fast.

Rapid setting thanks to the easy-action locking lever in the handle. Ergonomically designed, non-slip adjuster with a thumb recess for fast, safe setting of the slider.

Simple.

Quick adjustment from outside, no disassembly of the torque wrench required, with two adjustment points for the maximum & minimum values.


Technologies and features.




QuickRelease

The QuickRelease technology ensures tools cannot be inadvertently lost - while enabling rapid, safe tool changes.

Technical Drawing.





Technical Attributes.

Logistics data.

Measuring range N·m	30-150 N·m	Depth mm (IFS)	455
Measuring range ft·lb	25-110 ft·lb	Width mm (IFS)	43

Product data sheet 21.03.2024

b128 mmLength (packed, mm)475b241 mmWidth (packed, mm)45Size15Height (packed, mm)45Height mm (h1)23 mmVolume (packed, dm3)0.961875 dm3Height mm (h2)18 mmArt. no.50204115Length mm (L)452,5 mmWeight (gross, kg)1,378LF387 mmWeight PAP (kg)0,000MA N·m30 N·mWeight PVC (kg)0,011Scale division [E1]5 N·mCountry of originGERMANYScale division [E2]5 ft·lbRegion of originNordrhein-WestfalenWEEE/ElektroGnicht ear-pflichtigQuadth of the statiff no.82041100Faching standard1Yeight1268 g	External square drive (inch)	1/2	Height mm (IFS)	40
Size15Height (packed, mm)45Height mm (h1)23 mmVolume (packed, dm3)0.961875 dm3Height mm (h2)18 mmArt. no.50204115Length mm (L)452,5 mmWeight (gross, kg)1,378LF387 mmWeight PAP (kg)0,000MA N·m30 N·mWeight PVC (kg)0,011Nominal value N·m150 N·mGTIN4018754268955Scale division [E1]5 N·mCountry of originGERMANYScale division [E2]5 ft·lbRegion of originNordrhein-WestfalenWEEE/ElektroGnicht ear-pflichtigCustoms tariff no.82041100Packing standard111	b1	28 mm	Length (packed, mm)	475
Height mm (h1)23 mmVolume (packed, dm3)0.961875 dm3Height mm (h2)18 mmArt. no.50204115Length mm (L)452,5 mmWeight (gross, kg)1,378LF387 mmWeight PAP (kg)0,000MA N·m30 N·mWeight PVC (kg)0,011Nominal value N·m150 N·mGTIN4018754268955Scale division [E1]5 N·mCountry of originGERMANYScale division [E2]5 ft·lbRegion of originNordrhein-WestfalenWEEE/ElektroGnicht ear-pflichtigCustoms tariff no.82041100Backing standard1	b2	41 mm	Width (packed, mm)	45
Height mm (h2)18 mmArt. no.50204115Length mm (L)452,5 mmWeight (gross, kg)1,378LF387 mmWeight PAP (kg)0,000MA N·m30 N·mWeight PVC (kg)0,011Nominal value N·m150 N·mGTIN4018754268955Scale division [E1]5 N·mCountry of originGERMANYScale division [E2]5 ft·lbRegion of originNordrhein-WestfalenKetter Ketter Kette	Size	15	Height (packed, mm)	45
Length mm (L)452,5 mmWeight (gross, kg)1,378LF387 mmWeight PAP (kg)0,000MA N·m30 N·mWeight PVC (kg)0,011Nominal value N·m150 N·mGTIN4018754268955Scale division [E1]5 N·mCountry of originGERMANYScale division [E2]5 ft·lbRegion of originNordrhein-WestfalenKetter KurdenNordrhein-WestfalenWetter/ElektroGNordrhein-WestfalenKurdenKetter Kurden100100KurdenBacking standard1	Height mm (h1)	23 mm	Volume (packed, dm3)	0.961875 dm3
LF387 mmWeight PAP (kg)0,000MA N·m30 N·mWeight PVC (kg)0,011Nominal value N·m150 N·mGTIN4018754268955Scale division [E1]5 N·mCountry of originGERMANYScale division [E2]5 ft·lbRegion of originNordrhein-WestfalenKEEE/ElektroGnicht ear-pflichtig82041100LFPacking standard1	Height mm (h2)	18 mm	Art. no.	50204115
MA N·m30 N·mWeight PVC (kg)0,011Nominal value N·m150 N·mGTIN4018754268955Scale division [E1]5 N·mCountry of originGERMANYScale division [E2]5 ft·lbRegion of originNordrhein-WestfalenWEEE/ElektroGnicht ear-pflichtig2041100Luttor Luttor Lutt	Length mm (L)	452,5 mm	Weight (gross, kg)	1,378
Nominal value N·m150 N·mGTIN4018754268955Scale division [E1]5 N·mCountry of originGERMANYScale division [E2]5 ft·lbRegion of originNordrhein-WestfalenWEEE/ElektroGnicht ear-pflichtig82041100LuePacking standard1	LF	387 mm	Weight PAP (kg)	0,000
Scale division [E1]5 N·mCountry of originGERMANYScale division [E2]5 ft·lbRegion of originNordrhein-WestfalenWEEE/ElektroGnicht ear-pflichtigCustoms tariff no.82041100Packing standard1	MA N·m	30 N·m	Weight PVC (kg)	0,011
Scale division [E2] 5 ft·lb Region of origin Nordrhein-Westfalen WEEE/ElektroG nicht ear-pflichtig Customs tariff no. 82041100 Packing standard 1	Nominal value N·m	150 N·m	GTIN	4018754268955
WEEE/ElektroGnicht ear-pflichtigCustoms tariff no.82041100Packing standard1	Scale division [E1]	5 N·m	Country of origin	GERMANY
Customs tariff no.82041100Packing standard1	Scale division [E2]	5 ft·lb	Region of origin	Nordrhein-Westfalen
Packing standard 1			WEEE/ElektroG	nicht ear-pflichtig
			Customs tariff no.	82041100
Weight 1268 g			Packing standard	1
			Weight	1268 g

Variants.

Art. no.	Art. no. (ERP)	Description	GTIN
50204115	721QR/15 QUICK	MANOSKOP® torque wrench No. 721QR/15 Quick Measuring r. 30-150N·m Drive 1/2 L. 452,5mm	4018754268955
50204120	721QR/20 QUICK	MANOSKOP® torque wrench No. 721QR/20 Quick Measuring r. 40-200N∙m Drive 1/2 L. 482mm	4018754268962

GTIN-Code.



Product data sheet 21.03.2024

Images.



STAHLWILLE Eduard Wille GmbH & Co. KG

Lindenallee 27 · 42349 Wuppertal · Germany · Phone: +49 202 4791-0 · Fax: +49 202 4791-200 info@stahlwille.de · www.stahlwille.com · Copyright by STAHLWILLE Eduard Wille GmbH & Co. KG, Wuppertal Copyright by STAHLWILLE Eduard Wille GmbH & Co. KG, Wuppertal