

SERVICE-MANOSKOP torque wrench

730R Quick



Art.No. **96504012**
GTIN **4018754269501**
Model **730R/12 QUICK**

Label.

SERVICE-MANOSKOP torque wrench No. 730R Quick Measuring r. 25-130N·m Drive 1/2 L. 475mm

Features.

- releasing
- No reset to "0" necessary, as measuring element is only loaded during the tightening process
- receptacle for interchangeable plug-in tools
- QuickRelease safety lock
- Flash adjustment by easy-to-operate clamping lever in the handle
- ergonomically shaped, non-slip adjustment element with thumb recess
- optimised ball handle for fatigue-free working
- double stop signal
- double scale N·m/ft·lb or N·m/in·lb
- on request also available as N·m version only without double scale
- left-hand tightening by turning over the plug-in tools
- further loads after releasing or loads against the functional direction, e.g. with stuck screws, do not affect the releasing mechanism, which is thus protected against damage
- calibration with the perfectControl® calibration device no. 7794 or the calibration system no. 7706. If necessary, readjustment without disassembly
- certificate according to DIN EN ISO 6789-2:2017
- display deviation $\pm 4\%$

Advantages.

25-130 N·m.

Product highlights.



Flexible rod principle.

Mechanical torque wrenches from STAHLWILLE have a wear-resistant trigger system with a flexible rod. In contrast to conventional torque wrenches with spiral springs, the STAHLWILLE system eliminates one key work step: once the fastener has been tightened, it is not necessary to reset the wrench to »0«.



Fast.

Rapid setting thanks to the easy-action locking lever in the handle. Ergonomically designed, non-slip adjuster with a thumb recess for fast, safe setting of the slider.



Simple.

Quick adjustment from outside, no disassembly of the torque wrench required, with two adjustment points for the maximum & minimum values.

Technical Attributes.

Measuring range N·m	25-130 N·m
Measuring range ft·lb	20-95 ft·lb
External square drive (inch)	1/2
Width mm (b)	52 mm
Height mm (h)	52 mm
Length mm (L)	475 mm
Scale division [E1]	2,5 N·m
Scale division [E2]	2,5 ft·lb

Logistics data.

Depth mm (IFS)	475
Width mm (IFS)	52
Height mm (IFS)	52
Length (packed, mm)	475
Width (packed, mm)	52
Height (packed, mm)	52
Volume (packed, dm ³)	1.2844 dm ³
Art. no.	96504012
Weight (gross, kg)	1,488
Weight PAP (kg)	0,000
Weight PVC (kg)	0,011
GTIN	4018754269501
Country of origin	GERMANY
Region of origin	Nordrhein-Westfalen
WEEE/ElektroG	nicht ear-pflichtig
Customs tariff no.	82041100
Packing standard	1
Weight	1488 g

Variants.

Art. no.	Art. no. (ERP)	Description	GTIN
96501054	730R/2-1 Quick	Torque wrench MANOSKOP® No. 730R Quick Measuring r. 2-10N·m Drive 1/4 L. 250mm	4018754339976
96504002	730R/2 QUICK	SERVICE-MANOSKOP torque wrench No. 730R Quick Measuring r. 4-20N·m Drive 3/8 L. 255mm	4018754311354
96504004	730R/4 QUICK	Torque wrench MANOSKOP® No. 730R Quick Measuring r. 8-40N·m Drive 3/8 L. 285mm	4018754311361
96504005	730R/5 QUICK	SERVICE-MANOSKOP torque wrench No. 730R Quick Measuring r. 6-50N·m Drive 3/8 L. 380mm	4018754269488
96504010	730R/10 QUICK	Torque wrench MANOSKOP® No. 730R Quick Measuring r. 20-100N·m Drive 1/2 L. 430mm	4018754269495
96504012	730R/12 QUICK	SERVICE-MANOSKOP torque wrench No. 730R Quick Measuring r. 25-130N·m Drive 1/2 L. 475mm	4018754269501
96504020	730R/20 QUICK	SERVICE-MANOSKOP torque wrench No. 730R Quick Measuring r. 40-200N·m Drive 1/2 L. 530mm	4018754269518
96504030	730R/30 QUICK	Torque wrench MANOSKOP® No. 730R Quick Measuring r. 60-300N·m Drive 1/2 L. 590mm	4018754326006
96504040	730R/40 QUICK	Torque wrench MANOSKOP® No. 730R Quick Measuring r. 80-400N·m Drive 3/4 L. 675mm	4018754269525
96504565	730RII/65 QUICK	Torque wrench MANOSKOP® No. 730R Quick Measuring r. 130-650N·m Drive 3/4 L. 1125mm	4018754269563

GTIN-Code.



Images.



STAHLWILLE Eduard Wille GmbH & Co. KG

Lindenallee 27 · 42349 Wuppertal · Germany · Phone: +49 202 4791-0 · Fax: +49 202 4791-200
info@stahlwille.de · www.stahlwille.com · Copyright by STAHLWILLE Eduard Wille GmbH & Co. KG, Wuppertal
Copyright by STAHLWILLE Eduard Wille GmbH & Co. KG, Wuppertal