

Torque wrench MANOSKOP®

730R Quick



Art.No. **96504010**
GTIN **4018754269495**
Model **730R/10 QUICK**

Label.

Torque wrench MANOSKOP® No. 730R Quick Measuring r. 20-100N·m Drive 1/2 L. 430mm

Features.

- releasing
- No reset to "0" necessary, as measuring element is only loaded during the tightening process
- receptacle for interchangeable plug-in tools
- QuickRelease safety lock
- Flash adjustment by easy-to-operate clamping lever in the handle
- ergonomically shaped, non-slip adjustment element with thumb recess
- optimised ball handle for fatigue-free working
- double stop signal
- double scale N-m/ft-lb or N-m/in-lb
- on request also available as N-m version only without double scale
- left-hand tightening by turning over the plug-in tools
- further loads after releasing or loads against the functional direction, e.g. with stuck screws, do not affect the releasing mechanism, which is thus protected against damage
- calibration with the perfectControl® calibration device no. 7794 or the calibration system no. 7706. If necessary, readjustment without disassembly
- certificate according to DIN EN ISO 6789-2:2017
- display deviation $\pm 4\%$

Advantages.

Releasing.

Product highlights.



Flexible rod principle.

Mechanical torque wrenches from STAHLWILLE have a wear-resistant trigger system with a flexible rod. In contrast to conventional torque wrenches with spiral springs, the STAHLWILLE system eliminates one key work step: once the fastener has been tightened, it is not necessary to reset the wrench to »0«.



Fast.

Rapid setting thanks to the easy-action locking lever in the handle. Ergonomically designed, non-slip adjuster with a thumb recess for fast, safe setting of the slider.



Simple.

Quick adjustment from outside, no disassembly of the torque wrench required, with two adjustment points for the maximum & minimum values.

Technical Attributes.

Measuring range N·m	20-100 N·m
External square drive (inch)	1/2
Width mm (b)	55 mm
Size	10
Size square socket [inside square drive]	9 x 12 mm
Height mm (h)	55 mm
Length mm (L)	430 mm

Logistics data.

Depth mm (IFS)	430
Width mm (IFS)	55
Height mm (IFS)	55
Length (packed, mm)	430
Width (packed, mm)	55
Height (packed, mm)	55
Volume (packed, dm ³)	1.30075 dm ³
Art. no.	96504010
Weight (gross, kg)	1,190
Weight PAP (kg)	0,000
Weight PVC (kg)	0,116
GTIN	4018754269495
Country of origin	GERMANY
Region of origin	Nordrhein-Westfalen
WEEE/ElektroG	nicht ear-pflichtig
Customs tariff no.	82041100
Packing standard	1
Weight	1190 g

Variants.

Art. no.	Art. no. (ERP)	Description	GTIN
96501054	730R/2-1 Quick	Torque wrench MANOSKOP® No. 730R Quick Measuring r. 2-10N·m Drive 1/4 L. 250mm	4018754339976
96504002	730R/2 QUICK	SERVICE-MANOSKOP torque wrench No. 730R Quick Measuring r. 4-20N·m Drive 3/8 L. 255mm	4018754311354
96504004	730R/4 QUICK	Torque wrench MANOSKOP® No. 730R Quick Measuring r. 8-40N·m Drive 3/8 L. 285mm	4018754311361
96504005	730R/5 QUICK	SERVICE-MANOSKOP torque wrench No. 730R Quick Measuring r. 6-50N·m Drive 3/8 L. 380mm	4018754269488
96504010	730R/10 QUICK	Torque wrench MANOSKOP® No. 730R Quick Measuring r. 20-100N·m Drive 1/2 L. 430mm	4018754269495
96504012	730R/12 QUICK	SERVICE-MANOSKOP torque wrench No. 730R Quick Measuring r. 25-130N·m Drive 1/2 L. 475mm	4018754269501
96504020	730R/20 QUICK	SERVICE-MANOSKOP torque wrench No. 730R Quick Measuring r. 40-200N·m Drive 1/2 L. 530mm	4018754269518
96504030	730R/30 QUICK	Torque wrench MANOSKOP® No. 730R Quick Measuring r. 60-300N·m Drive 1/2 L. 590mm	4018754326006
96504040	730R/40 QUICK	Torque wrench MANOSKOP® No. 730R Quick Measuring r. 80-400N·m Drive 3/4 L. 675mm	4018754269525
96504565	730R/65 QUICK	Torque wrench MANOSKOP® No. 730R Quick Measuring r. 130-650N·m Drive 3/4 L. 1125mm	4018754269563

GTIN-Code.



Images.



STAHlwILLE Eduard Wille GmbH & Co. KG

Lindenallee 27 · 42349 Wuppertal · Germany · Phone: +49 202 4791-0 · Fax: +49 202 4791-200
info@stahlwille.de · www.stahlwille.com · Copyright by STAHlwILLE Eduard Wille GmbH & Co. KG, Wuppertal
Copyright by STAHlwILLE Eduard Wille GmbH & Co. KG, Wuppertal